

**IN THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1-25 (Canceled).

26. (Currently amended) A semiconductor device comprising:

a substrate having an insulating surface;

a thin film transistor formed over the substrate, the thin-film transistor comprising a gate electrode formed over the substrate; a first insulating layer, wherein a portion of said first insulating layer is formed on said gate electrode; a channel formation region formed in a semiconductor layer having an amorphous structure; source and drain regions, each of the source and drain regions comprising a semiconductor layer including impurities of a first conductivity type, formed over the semiconductor layer having the amorphous structure;

a second insulating layer comprising an inorganic material and formed on the semiconductor layer having the amorphous structure and the semiconductor layer containing the impurities of a first conductivity type so as to be in contact with at least a part of the channel formation region;

a pixel electrode ~~formed in contact with~~ over the first insulating layer;

a source wiring formed on the source region;

a drain wiring formed on the drain region and overlapping with a portion of the pixel electrode;

a storage capacitor comprising a storage capacitor wiring comprising the same material as that of the gate electrode, a portion of the first insulating layer on the storage capacitor wiring and a portion of the pixel electrode ~~on the first insulating layer~~; and

an input terminal portion formed along an end portion of the substrate and electrically connected to the source wiring;

wherein the input terminal portion comprises a first layer comprising a same material as the gate electrode, a second layer comprising a same material as the pixel electrode,

wherein the source wiring is ~~formed on~~ electrically connected to the second layer of said input terminal portion,

wherein the storage capacitor wiring is completely covered by the pixel electrode, and

wherein an edge of the second layer of said input terminal portion is aligned with an edge of the substrate [[.]] , and

wherein the second insulating layer overlaps with a portion of the pixel electrode.

27. (Currently amended) A semiconductor device comprising:

a substrate having an insulating surface;

a thin film transistor formed over the substrate, the thin-film transistor comprising a gate electrode formed over the substrate; a first insulating layer, wherein a portion of said first insulating layer is formed on said gate electrode; a channel formation region formed in a semiconductor layer having an amorphous structure; source and drain regions, each of the source and drain regions comprising a semiconductor layer including impurities of first conductivity type, formed over the semiconductor layer having the amorphous structure;

a second insulating layer comprising an inorganic material and formed on the semiconductor layer having the amorphous structure and the semiconductor layer containing the impurities of first conductivity type so as to be in contact with at least a part of the channel formation region;

a pixel electrode formed in contact with the first insulating layer;

a storage capacitor comprising a storage capacitor wiring comprising the same material as that of the gate electrode, a portion of the first insulating layer on the storage capacitor wiring and a portion of the pixel electrode ~~on the first insulating layer~~; and

an input terminal portion formed along an end portion of the substrate and electrically connected to a first wiring;

wherein the input terminal portion comprises a first layer comprising a same material as the gate electrode and a second layer comprising a same material as the pixel electrode in contact with the first layer through a contact hole formed only in the first insulating layer,

wherein a portion of the first wiring is formed on the second layer of said input terminal portion,

wherein the storage capacitor wiring is completely covered by the pixel electrode, and

wherein an edge of the second layer of said input terminal portion is aligned with an edge of the substrate.

28. (Currently amended) A semiconductor device comprising:

a substrate having an insulating surface;

a thin film transistor formed over the substrate, the thin-film transistor comprising a gate electrode formed over the substrate; a first insulating layer, wherein a portion of said first insulating layer is formed on said gate electrode; a channel formation region formed in a semiconductor layer having an amorphous structure; source and drain regions, each of the source and drain regions comprising a semiconductor layer including impurities of first conductivity type, formed over the semiconductor layer having the amorphous structure;

a pixel electrode ~~formed in contact with~~ over the first insulating layer;

a second insulating layer comprising an inorganic material and ~~formed on~~ overlapping with a portion of the pixel electrode and the semiconductor layer having the amorphous structure and the semiconductor layer containing the impurities of first conductivity type so as to be in contact with at least a part of the channel formation region;

a storage capacitor comprising a storage capacitor wiring comprising the same material as that of the gate electrode, a portion of the first insulating layer on the storage capacitor wiring and a portion of the pixel electrode ~~on the first insulating layer~~; and

an input terminal portion formed along an end portion of the substrate and electrically connected to a first wiring;

wherein the input terminal portion comprises a first layer comprising a same material as the gate electrode, a second layer comprising a same material as the pixel electrode, and

wherein the first wiring is ~~formed on~~ electrically connected to the second layer of said input terminal portion,

wherein each of the gate electrode, the storage capacitor wiring and the first layer has a tapered portion formed on at least an end portion thereof,

wherein the storage capacitor wiring is completely covered by the pixel electrode, and

wherein an edge of the second layer of said input terminal portion is aligned with an edge of the substrate.

29. (Canceled)

30. (Currently amended) A semiconductor device comprising:

a substrate having an insulating surface;

a thin film transistor formed over the substrate, the thin-film transistor comprising a gate electrode formed over the substrate; a first insulating layer, wherein a portion of said first insulating layer is formed on said gate electrode; a channel formation region formed in a semiconductor layer having an amorphous structure; source and drain regions, each of the source and drain regions comprising a semiconductor layer including impurities of first conductivity type, formed over the semiconductor layer having the amorphous structure;

a second insulating layer comprising an inorganic material and formed on the semiconductor layer having the amorphous structure and the semiconductor layer containing the impurities of first conductivity type so as to be in contact with at least a part of the channel formation region;

a pixel electrode formed in contact with the first insulating layer;

a storage capacitor comprising a storage capacitor wiring comprising the same material as that of the gate electrode, a portion of the first insulating layer on the storage capacitor wiring and the pixel electrode ~~on the first insulating layer~~; and

an input terminal portion formed along an end portion of the substrate and electrically connected to a first wiring;

wherein the input terminal portion comprises a first layer comprising a same material as the gate electrode and a second layer comprising a same material as the pixel electrode in contact with the first layer through a contact hole formed only in the first insulating layer, and

wherein a portion of the first wiring is formed on the second layer of said input terminal portion,

wherein each of the gate electrode, the storage capacitor wiring and the first layer has a tapered portion formed on at least an end portion thereof,

wherein the storage capacitor wiring is completely covered by the pixel electrode, and

wherein an edge of the second layer of said input terminal portion is aligned with an edge of the substrate.

31. (Currently amended) A semiconductor device comprising:

a substrate having an insulating surface;

a thin film transistor formed over the substrate, the thin-film transistor comprising a gate electrode formed over the substrate; a first insulating layer, wherein a portion of said first insulating layer is formed on said gate electrode; a channel formation region formed in a semiconductor layer having an amorphous structure; source and drain regions, each of the source and drain regions comprising a semiconductor layer including impurities of a first conductivity type, formed over the semiconductor layer having the amorphous structure;

a second insulating layer comprising an inorganic material and formed on the semiconductor layer having the amorphous structure and the semiconductor layer containing the impurities of a first conductivity type so as to be in contact with at least a part of the channel formation region;

a pixel electrode ~~formed in contact with~~ over the first insulating layer;

a source wiring formed on the source region;

a drain wiring formed on the drain region and overlapping with a portion of the pixel electrode;

a storage capacitor comprising a storage capacitor wiring comprising the same material as that of the gate electrode, a portion of the first insulating layer on the storage capacitor wiring and a portion of the pixel electrode ~~on the first insulating layer~~; and

an input terminal portion formed along an end portion of the substrate and electrically connected to the source wiring;

wherein the input terminal portion comprises a first layer comprising a same material as the gate electrode, a second layer comprising a same material as the pixel electrode,

wherein the source wiring is ~~formed on~~ electrically connected to the second layer of said input terminal portion, ~~[[and]]~~

wherein an edge of the second layer of said input terminal portion is aligned with an edge of the substrate~~[[.]], and~~

wherein the second insulating layer overlaps with a portion of the pixel electrode.

32. (Currently amended) A semiconductor device comprising:

a substrate having an insulating surface;

a thin film transistor formed over the substrate, the thin-film transistor comprising a gate electrode formed over the substrate; a first insulating layer, wherein a portion of said first insulating layer is formed on said gate electrode; a channel formation region formed in a semiconductor layer having an amorphous structure; source and drain regions, each of the source and drain regions comprising a semiconductor layer including impurities of first conductivity type, formed over the semiconductor layer having the amorphous structure;

a second insulating layer comprising an inorganic material and formed on the semiconductor layer having the amorphous structure and the semiconductor layer containing the impurities of first conductivity type so as to be in contact with at least a part of the channel formation region;

a pixel electrode formed in contact with the first insulating layer;

a storage capacitor comprising a storage capacitor wiring comprising the same material as that of the gate electrode, a portion of the first insulating layer on the storage capacitor wiring and a portion of the pixel electrode ~~on the first insulating layer~~; and

an input terminal portion formed along an end portion of the substrate and electrically connected to a first wiring;

wherein the input terminal portion comprises a first layer comprising a same material as the gate electrode and a second layer comprising a same material as the pixel electrode in contact with the first layer through a contact hole formed only in the first insulating layer,

wherein a portion of the first wiring is formed on the second layer of said input terminal portion, and

wherein an edge of the second layer of said input terminal portion is aligned with an edge of the substrate.

33. (Currently amended) A semiconductor device comprising:

a substrate having an insulating surface;

a thin film transistor formed over the substrate, the thin-film transistor comprising a gate electrode formed over the substrate; a first insulating layer, wherein a portion of said first insulating layer is formed on said gate electrode; a channel formation region formed in a semiconductor layer having an amorphous structure; source and drain regions, each of the source and drain regions comprising a semiconductor layer including impurities of first conductivity type, formed over the semiconductor layer having the amorphous structure;

a pixel electrode ~~formed in contact with~~ over the first insulating layer;

a second insulating layer comprising an inorganic material and ~~formed on~~ overlapping with a portion of the pixel electrode and the semiconductor layer having the amorphous structure and the semiconductor layer containing the impurities of first conductivity type so as to be in contact with at least a part of the channel formation region;



a storage capacitor comprising a storage capacitor wiring comprising the same material as that of the gate electrode, a portion of the first insulating layer on the storage capacitor wiring and a portion of the pixel electrode ~~on the first insulating layer~~; and

an input terminal portion formed along an end portion of the substrate and electrically connected to a first wiring;

wherein the input terminal portion comprises a first layer comprising a same material as the gate electrode, a second layer comprising a same material as the pixel electrode, and

wherein the first wiring is ~~formed on~~ electrically connected to the second layer of said input terminal portion,

wherein each of the gate electrode, the storage capacitor wiring and the first layer has a tapered portion formed on at least an end portion thereof, and

wherein an edge of the second layer of said input terminal portion is aligned with an edge of the substrate.

34. (Currently amended) A semiconductor device comprising:

a substrate having an insulating surface;

a thin film transistor formed over the substrate, the thin-film transistor comprising a gate electrode formed over the substrate; a first insulating layer, wherein a portion of said first insulating layer is formed on said gate electrode; a channel formation region formed in a semiconductor layer having an amorphous structure; source and drain regions, each of the source and drain regions comprising a semiconductor layer including impurities of first conductivity type, formed over the semiconductor layer having the amorphous structure;

a second insulating layer comprising an inorganic material and formed on the semiconductor

layer having the amorphous structure and the semiconductor layer containing the impurities of first conductivity type so as to be in contact with at least a part of the channel formation region;

a pixel electrode formed in contact with the first insulating layer;

a storage capacitor comprising a storage capacitor wiring comprising the same material as that of the gate electrode, a portion of the first insulating layer on the storage capacitor wiring and the pixel electrode ~~on the first insulating layer~~; and

an input terminal portion formed along an end portion of the substrate and electrically connected to a first wiring;

wherein the input terminal portion comprises a first layer comprising a same material as the gate electrode and a second layer comprising a same material as the pixel electrode in contact with the first layer through a contact hole formed only in the first insulating layer, and

wherein a portion of the first wiring is formed on the second layer of said input terminal portion,

wherein each of the gate electrode, the storage capacitor wiring and the first layer has a tapered portion formed on at least an end portion thereof, and

wherein an edge of the second layer of said input terminal portion is aligned with an edge of the substrate.

35. (Previously presented) A semiconductor device according to claim 26, wherein the semiconductor device is selected from a group consisting of a personal computer, a video camera, a portable information terminal, a digital camera, a digital video disc player, an electronic play device and a television.

36. (Previously presented) A semiconductor device according to claim 27, wherein the semiconductor device is selected from a group consisting of a personal computer, a video camera, a portable information terminal, a digital camera, a digital video disc player, an electronic play device and a television.

37. (Previously presented) A semiconductor device according to claim 28, wherein the semiconductor device is selected from a group consisting of a personal computer, a video camera, a portable information terminal, a digital camera, a digital video disc player, an electronic play device and a television.

38. (Previously presented) A semiconductor device according to claim 30, wherein the semiconductor device is selected from a group consisting of a personal computer, a video camera, a portable information terminal, a digital camera, a digital video disc player, an electronic play device and a television.

39. (Previously presented) A semiconductor device according to claim 31, wherein the semiconductor device is selected from a group consisting of a personal computer, a video camera, a portable information terminal, a digital camera, a digital video disc player, an electronic play device and a television.

40. (Previously presented) A semiconductor device according to claim 32, wherein the semiconductor device is selected from a group consisting of a personal computer, a video camera, a portable information terminal, a digital camera, a digital video disc player, an electronic play device

and a television.

41. (Previously presented) A semiconductor device according to claim 33, wherein the semiconductor device is selected from a group consisting of a personal computer, a video camera, a portable information terminal, a digital camera, a digital video disc player, an electronic play device and a television.

42. (Previously presented) A semiconductor device according to claim 34, wherein the semiconductor device is selected from a group consisting of a personal computer, a video camera, a portable information terminal, a digital camera, a digital video disc player, an electronic play device and a television.